

BSC-24 Noise Barrier/Sound Absorber Composite

The barrier septum configuration offers the benefits of both sound absorption and noise barrier in one product. A non-reinforced 1-lb psf loaded vinyl barrier is sandwiched between two layers of quilted fiberglass absorbers. When tested to ATSM E84, the composite has a **Class 1 or A** flammability rating, and is commonly used in plenums.



- Rolls are available 4' wide up to 25' long
- Available die-cut to 2' x 4' to lay on top of standard ceiling tiles
- Hi-temp, economy Scrim facing on both sides

Applications:

Typical uses include lining stud cavity of staggered stud drywall wall construction, or laid on top of ceiling tiles to improve transmission loss. Also may be suspended from roof deck to drywall to close gaps between rooms to prevent noise flanking over the top of the partition wall. Also used over existing walls in mechanical rooms or similar.

Product Data:

Description	1" scrim faced quilted fiberglass/ 1LB-psf non-reinforced loaded vinyl barrier/ 1" scrim faced quilted fiberglass
Flammability	Flame Spread: 5.07 Smoke density: .45
Nominal thickness	2.00"
Temperature range	-40° to +240° F
Standard size	48" x 25'
Weight	1.4 LB psf

Acoustical Performance:

Sound Transmission Loss

Product	OCTAVE BAND FREQUENCIES (Hz)						STC
	125	250	500	1000	2000	4000	
BSC-24	12	16	27	40	44	43	29

ASTM E-90 & E 413

Sound Absorption data

Product	OCTAVE BAND FREQUENCIES (Hz)						NRC
	125	250	500	1000	2000	4000	
BSC-24							



NOISE BARRIERS

Spec Data Sheet

BSC-SERIES
NOISE BARRIERS/SOUND ABSORBER
COMPOSITES

BSC-24	.19	.99	.96	.80	.57	.33	.85
--------	-----	-----	-----	-----	-----	-----	-----

ASTM C 423

